

SR8002 AV RECEIVER



Specifications

- THX Select2 certified Current Feedback AV-Receiver delivering 7x 125 Watts rms
- Dolby Digital Plus, Dolby TrueHD, DTS HD and 7.1 Multichannel PCM for HD Audio
- 32-bit DSP with THX Surround EX, DD-EX, DTS-ES, DTS96/24, CSII and DPL IIx
- Audio enhancer for all compressed audio formats as MP-3, WAV, AAC, etc
- Neural Surround, Dolby Headphone and Dolby Virtual Speaker II
- Room Acoustic Calibration with EQ by Audyssey for one touch speaker set-up
- Four HDMI1.3 input for digital audio and video including deep colour support
- Two HDMI1.3 output direct selectable via remote or RS232
- High grade video conversion with line memory up to HDMI level
- Huge Toroidal transformer with shielding for instant current delivery capability
- Copper plated chassis for lowest impedance grounding at any point
- Customized components for best sound performance in stereo and multichannel
- Two independent Zones for multi room/multi source audio and video (1x up to component level)
- RC101 for multi room use or as simple remote for main room included
- Surround Back speaker for multi room assignable
- Speaker C function for real bi-amping of front channel in 5.1 set-up
- Pure direct mode and Video off mode for best analogue sound
- Sound delay function to sync audio and video
- RS232c port, Flasher in, IR Flasher out, IR receiver in and DC triggers for system integration
- RC8001SR learnable system remote control with macro functions and backlit

Dimensions: W"x H"x D"(inches) 17-5/16" x 7-1/4" x 15-5/8"